


Atmospheric Optical Communications

Architecture, System Design and Concept Demonstration of a Battlefield Agile-beam Optical Communication System

> Vincent W. S. Chan Jeffrey H. Shapiro Franco N. C. Wong

Laboratory for Information and Decision Systems
Research Laboratory of Electronics
Department of Electrical Engineering and Computer Science
Department of Aeronautics and Astronautics
Massachusetts Institute of Technology






Atmospheric Optical Communications




Far-away turbulence : scintillation Near-by turbulence : phase distortion



r_o = effective collector diameter

 $\tau_0 = r_0/v = time constant$


 θ_0 = isoplanatic angle



Boundary layer turbulence & bow shock creates rapid beam steering and poor strehl



Atmospheric Optical Wave Propagation



Free-Space vs. Atmospheric Propagation

- Molecular Constituents
- Atmospheric Turbulence
- Clouds, Fog, Snow, and Rain
- Smoke and Dust

Atmospheric Turbulence


- Refractive-Index Fluctuations
- Kolmogorov Inertial-Subrange Spatial Spectrum
- Taylor's Hypothesis (Frozen-Flow) Temporal Behavior

Extended Huygens-Fresnel Principle


- Mutual Coherence Function Behavior
- Scintillation Behavior


Line-of-Sight Propagation Phenomena

- Attenuation, Depolarization
- Beam Spread, Angular Spread




- Multipath Spread: intersymbol interference
- Doppler Spread: time-dependent fading








Atmospheric Optical Wave Propagation




The Beer-Lambert Law

Absorption, Scattering and Extinction




Atmospheric Turbulence


• $\Delta T \sim 1K$ leads to $\Delta n \sim 10^{-6}$



Modified Von Karman Spatial Spectrum








Quasimonochromatic, Scalar-Wave Propagation






Instantaneous Atmospheric Reciprocity










Green's Function Statistics








Beam Spread and Angular Spread








Scintillation: Log-Amplitude Variance







HORIZONTAL PATH LOG-AMPLITUDE VARIANCE

Horizontal Path Coherence Length






Fade Depths for Lognormal Statistics







$$\Phi_{\rm n}(\kappa) = 0.033 \, {\rm C}_{\rm n}^2 \, \kappa^{-11/3}$$

Kinetic Energy Associated with Large Eddies is Redistributed to Smaller Eddies Without Loss

$$r_0 = 0.185 \left\{ \frac{\lambda^2}{\sec(\zeta) \int C_n^2(h) dh} \right\}^{3/5}$$


Turbulence Intensity Coherence Length


$$\tau_{o} = 0.058 \left\{ \frac{\lambda^{2}}{\sec(\zeta) \int C_{n}^{2}(h) v^{5/3}(h) dh} \right\}^{3/5}$$
 Turbulence Time Constant



APPROVED FOR PUBLIC RELEASE, DISTRIBUTION UNLIMITED


Scintillation Statistical Models







Turbulence Mitigation Transmitter Techniques




- Tranmitter averaging
 - multiple transmitters (?)
 - dispersion

- Predistortion
 - reciprocity a concern



Turbulence Mitigation Receiver Techniques



Receiver aperture averaging

- photon bucket
- multiple incoherent receivers and power combining Incoherent combining gains as $N^{1/2}$


Coherent compensation

- deformable mirror, MEM
- coherent receiving array
- non-linear four-wave mixing

Coherent combining gains as N but more complex




Turbulence Mitigation Techniques




- •Time diversity
- Coding and interleaving
 - •long interleaver size a burden for high rates
 - •space-time coding
- •Frequency diversity
 - •complex and wideband
- Transport layer protocol




APD Multi-mode Receivers








Multi-mode EDFA Receivers





- LESS COMPLEX THAN ADAPTIVE OPTICS
- NO SERVO CONTROL (no Greenwood frequency dependence)
- REQUIRES DEVELOPMENT WORK
- KEY ISSUES

 FIBER COUPLING EFFICIENCY


 NOISE PENALTY


 DISPERSION

MIT



Multi-mode Coherent Receivers












Time Diversity Transmission








Frequency Diversity Transmission






$$|\lambda_1 - \lambda_2| > ? \text{ nm}$$

Optimum processing vs simple suboptimum combining




Outdoor-Path Test Bed Facilities




- High data rate (~1 Gb/s) 1.55-µm communication system
- Commercial off-the-shelf components and subsystems
- Interface with existing fiberoptic networks
- Mitigation techniques for handling naturally occurring atmospheric turbulence:
 - Spatial diversity reception
 - Time diversity transmission
 - Frequency diversity transmission



Experimental Concept Demonstration





- Outdoor link to handle prevailing atmospheric conditions
- Communication performance using transmitter and receiver diversity combining techniques and modulation protocols
- Verification of statistical models and system designs
- Feedback for system design/optimization research